

FROM: Law Office of David L. McEwing, PC

PO BOX 231324
HOUSTON, TEXAS 77023

TELEPHONE: (713) 514-0137
FACSIMILE: (713) 514-9840

EMAIL: DMCEWING@HOUSTON.PATENTLAW.COM
WWW.HOUSTONPATENTLAW.COM

TO: Timothy Kennedy

FAX No. .571-270-8068

Number of Pages (including cover) 3

DATE: August 5, 2009

RE: Application No. 10/559,601

COMMENTS: Attached are the further amended claims. I have marked the claims as "Currently amended", etc. Let me know of any further issues.

The contents of this facsimile are intended solely for the listed recipient and may contain privileged and confidential information. In the event that this message is transmitted to you in error, please call my office at (713) 514-0137 for instructions. Your cooperation and courtesy will be greatly appreciated.

Application No. 10/559,601

Filed 09/08/2006

68. (Currently amended) A method of curing concrete utilizing at least one heating component within uncured concrete by energizing the heating component with electrical power to resistively heat the concrete to a first temperature wherein the concrete has a fast rate of cure and a rate of compressive strength gain and then when the rate of compressive strength gain declines, modifying the electrical power to achieve a different second lower concrete temperature with a slower rate of cure.
69. (Currently amended) The method of claim 68 wherein the amount of electrical power is modified to achieve a maximum rate of compressive strength gain of the concrete.
88. (New) The method of claim 68 further comprising allowing the concrete to cool at a rate that achieves near maximum rate of strength gain for each temperature.
89. (New) The method of claim 68 further comprising allowing the concrete to cool at a rate to achieve a near maximum rate of gain in compressive strength at each temperature.
90. (New) A method for achieving the maximum compressive concrete strength in minimal cure time comprising the following steps:
- (a) heating concrete to a first temperature;
 - (b) monitoring changes in the rate of strength gain;
 - (c) controllably lowering the resistive heat to achieve a second lower concrete temperature;
 - (d) monitor the rate of strength gain at second temperature to maintain a maximum rate of strength gain;
 - (e) controllably decreasing the resistive heat when the rate of strength gain decreases;
 - (f) achieve a new third concrete temperature;
 - (g) monitor the rate of strength gain at the third temperature to maintain a

maximum rate of strength gain

- (h) controllably decreasing the resistive heat when the rate of strength gain decreases;
- (i) achieve a new fourth concrete temperature; and
- (j) monitor the rate of strength gain at the fourth temperature to maintain a maximum rate of strength gain.

91. (New) The method of claim 93 further comprising:

- (a) heating the concrete at 50° C for a time wherein the concrete reaches its maximum rate of strength gain;
- (b) controllably reducing the heat to 35° C;
- (c) controllably reducing the heat to curing at 12.5° C; and
- (d) controllably reduce the heat 5° C.